

Ultra Encode SDI Technical Specifications

Copyright (c) 2011–2025 [Magewell Electronics Co., Ltd.](#) All rights reserved.

Specifications are based on current hardware, firmware and software revisions, and are subject to change without notice.

NDI® is trademark or registered trademark of Vizrt NDI AB.

Revised on 07/11/2025

Input & Loop-through

- SDI
 - Supports SD (ST 259)/HD (ST 292)/3Ga (ST 425)/3Gb (ST 425)/3Gb-DL(ST 425)/3Gb-DS(ST 425) standards
 - Typical resolution/frame rate:
 - 2048x1080p/2048x1080i 23.98/24/25/29.97/30/47.95/48/50/59.94/60
 - 1920x1080p/1920x1080i 23.98/24/25/29.97/30/47.95/48/50/59.94/60
 - 1280x720p 25/29.97/30/50/59.94/60
 - 720x576 25p/50i (PAL SD)
 - 720x480 29.97p/59.94i (NTSC SD)
 - Color sampling: YCbCr 10-bit 4:2:2, YCbCr 10-bit 4:4:4, YCbCr 12-bit 4:2:2, YCbCr 12-bit 4:4:4
- Audio
 - SDI embedded audio: 16-Channel, 24-bit, 192kHz sample rate
 - Audio from 3.5 mm LINE IN: 2-Channel, 24-bit, 192kHz sample rate

Encode

- Video
 - Bitrate: 16Mbps
 - Dual-stream encoding: main stream and sub stream
 - Main stream Resolution/frame rate:
 - 2048x1080p/1920x1200p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1920x1080p/1920x720p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1664x936p/1600x1200p/1600x900p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1440x1080p/1440x900p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1280x1024p/1280x960p/1280x800p/1280x720p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1024x768p 60/59.94/50/30/29.97/25/24/15/10/5
 - 960x540p/800x600p 60/59.94/50/30/29.97/25/24/15/10/5
 - 768x576p/720x576p/720x540p/720x480p 60/59.94/50/30/29.97/25/24/15/10/5
 - 640x480p/640x360p 60/59.94/50/30/29.97/25/24/15/10/5
 - 480x360p/480x270p 60/59.94/50/30/29.97/25/24/15/10/5
 - Native CEA-608/608 over 708 captions
 - Sub stream
 - Supports enabling/disabling sub stream
 - Resolution/frame rate:
 - 1920x1080p/1920x720p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1664x936p/1600x1200p/1600x900p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1440x1080p/1440x900p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1280x1024p/1280x960p/1280x800p/1280x720p 60/59.94/50/30/29.97/25/24/15/10/5
 - 1024x768p 60/59.94/50/30/29.97/25/24/15/10/5
 - 960x540p/800x600p 60/59.94/50/30/29.97/25/24/15/10/5
 - 768x576p/720x576p/720x540p/720x480p 60/59.94/50/30/29.97/25/24/15/10/5
 - 640x480p/640x360p 60/59.94/50/30/29.97/25/24/15/10/5
 - 480x360p/480x270p 60/59.94/50/30/29.97/25/24/15/10/5
 - H.264/H.265 (HEVC) Codec:
 - System timecode or RP-188 standard timecode for SEI Message setting
 - H.265 (HEVC) SEI message supports carrying interlacing signal mark
 - Video aspect ratio conversion
- Audio
 - 2-channel AAC audio
 - Bitrate: 256/192/128/96/64/48/32/16 kbps
 - Output source embedded audio and line in through LINE OUT

Live stream

- Natively supports streaming to:
 - Twitch
 - YouTube, publishing to timeline or a new event and setting “made for kids”
 - Facebook, enabling backup stream and publishing to timeline or a new event
- Supports streaming protocols:
 - RTSP
 - RTMP/RTMPS
 - SRT Caller/SRT Listener
 - NDI HX2
 - HLS
 - TS over UDP/TS over RTP
 - TVU ISSP
- Supports sessions over the same streaming protocol, such as
 - Up to 6 sessions of TS over RTP and TS over UDP simultaneously
 - Up to 6 sessions of SRT Caller and SRT Listener simultaneously, containing one SRT Listener session at most (max 8 clients simultaneously)
 - Up to 6 sessions of RTMP and RTMPS simultaneously
- Supports streaming only 1 session of HLS, RTSP, or NDI HX2
- Supports specifying a video stream and an audio stream for each streaming session
- Supports NDI 6.1.1

Web UI

- Access Web UI via PC and smartphone
- View real-time device status
- Preview encoded video
- Set input sources
- Customize encoding parameters
- Manage streaming destinations, start/stop streaming, view streaming status
- Set up to 8 overlays for each stream, including text, picture, and clock
- Update firmware
- Supports registering Magewell Control Hub for centralized management
- Supports Microsoft Edge/Firefox/Chrome/Safari/Opera web browsers

API

- Provides APIs for 3rd party control system

Network Connections

- Ethernet: 1x RJ45 port, 10/100/1000 Mbps Base-T
- Wi-Fi: 802.11 a/b/g/n/ac, Station and AP modes supported
- 4G/5G USB modem (not supplied)
- USB Net

Input/Output Ports

- 2 x SD/HD/3G BNC ports
 - 1 x Input
 - 1 x Loop-through
- 1 x 3.5mm LINE IN
- 1 x 3.5mm LINE OUT
- 1 x USB Type-A

LED Indicators

- LEDs indicating the status of power, input signal, streaming, Ethernet and Wi-Fi connection

Power Supply and Consumption

- DC 5V/3A
- Max power consumption: ~7.16W

Form Factor

- 106.6mm x 106.2mm x 25mm

Accessories

- 1 x 5V Power Adapter
- 1 x USB Type A to Type B cable
- 1 x Wi-Fi Antenna
- 1 x T-bracke

Screw Mounting Hole

- 2 x M3 threaded hole
- A standard 1/4"-20 socket provided by T-bracket

Working Environment

- Operating temperature: 0 to 40 deg C
- Storage temperature: –20 to 40 deg C
- Relative humidity: 5% to 90% non-condensing